

Technische Specificaties: Sloop- en sorteergrijpers

Revisie: Dec 2020

		S75-D	S100-D	S150-D	S200-D	S300-D	S400-D	S450-D	S452-D	S502-D	S603-D	S803-D	S804-D	S903-D	S904-D	S1003-D	S1004-D
Klasse Graafmachine	ton	0,7-1,2	1-2	1,5-3	2,5-4	2,5-5	4-6	5-8	6-11	7-12	10-16	12-20	12-20	13-20	13-20	16-20	16-20
Gewicht	kg	75	90	140	240	280	350	400	450	600	840	1000	990	1040	1030	1070	1060
Werkdruk max.	bar	300	300	300	300	300	300	300	320	350	350	350	350	350	350	350	350
Werkdruk Rotatie min.	bar	170	170	170	170	170	190	190	190	190	190	190	190	190	190	190	190
Werkdruk Rotatie max.	bar	210	210	210	210	210	210	210	210	210	210	210	210	210	210	210	210
Olie flow max.	l/min.	15	20	25	35	35	40	50	70	90	100	120	120	120	120	120	120
Olie flow Rotatie max.	l/min.	5	5	10	10	10	12	12	15	15	25	25	25	25	25	25	25
Schaalbreedte	mm	300	350	450	500	500	600	700	700	600	800	800	800	900	900	1000	1000
Spreid geopend	mm	600	770	750	1160	1160	1400	1500	1550	1800	1800	1950	1950	1950	1950	1950	1950
Hoogte	mm	600	610	700	850	850	950	1000	1100	1150	1200	1300	1300	1300	1300	1300	1300
Inhoud	ltr.	30	40	70	100	100	150	200	200	300	400	500	500	600	600	700	700
Sluitkracht	kn	6	7	15	20	20	23	24	24	30	35	46	46	46	46	46	46
Slangaansluiting knijpfunctie	-	L10	L10	S12	S12	S12	S12	S12	S16	S16	S20	S20	S20	S20	S20	S20	S20
Slangaansluiting draaifunctie	-	L10	L10	L10	L10	L10	L10	L10	S12	S12	S16	S16	S16	S16	S16	S16	S16

		S1102-D	S1104-D	S1202-D	S1204-D	S1402-D	S1404-D	S1702-D	S1802-D	S1900-D	S2500-D	S2700-D	S3000-D	S4000-D	S4500-D	S5003-D	S8000-D	S13000-D
Klasse Graafmachine	ton	16-25	16-25	17-28	17-28	20-28	20-28	23-30	24-35	25-38	28-50	30-50	35-50	40-65	45-80	45-100	70-120	100-200
Gewicht	kg	1400	1350	1500	1450	1600	1550	1750	1800	1900	2500	2700	3000	4000	4200	5000	7250	13000
Werkdruk max.	bar	350	350	350	350	350	350	350	350	350	350	350	350	350	350	350	350	350
Werkdruk Rotatie min.	bar	190	190	190	190	190	190	190	190	190	190	190	190	190	190	190	190	190
Werkdruk Rotatie max.	bar	210	210	210	210	210	210	210	210	210	210	210	210	250	250	250	250	250
Olie flow max.	l/min.	150	150	160	160	170	170	170	170	180	200	200	200	250	250	300	320	350
Olie flow Rotatie max.	l/min.	35	35	35	35	35	35	35	35	35	35	35	35	40	40	60	70	100
Schaalbreedte	mm	900	900	1000	1000	1200	1200	1200	1200	1200	1200	1360	1500	1500	1500	1500	1800	1800
Spreid geopend	mm	2100	2100	2100	2100	2100	2100	2250	2400	2200	2200	2200	2400	2850	2850	3000	3800	4400
Hoogte	mm	1500	1500	1500	1500	1500	1500	1500	1550	1650	1700	1750	1800	1800	1800	2150	2250	3000
Inhoud	ltr.	750	750	800	800	850	850	900	950	900	1000	1100	1300	1500	1500	1600	3600	4600
Sluitkracht	kn	55	55	68	68	68	68	80	80	80	90	90	90	110	110	130	150	180
Slangaansluiting knijpfunctie	-	S25	S25	S25	S25	S25	S25	S25	S25	S25	S30	S30	S30	SAE	SAE	SAE	SAE	SAE
Slangaansluiting draaifunctie	-	S16	S16	S16	S16	S16	S16	S16	S16	S16	S16	S16	S16	S20	S20	S20	S25	S25